



LionEight ELD

Instruction Manual for Drivers




Table of Contents

Installation & Connection

Install the LionEight ELD device in your vehicle	3
Install the LionEight ELD App	4
Login to the LionEight ELD App and select a vehicle	4-5
Complete Pre-Trip DVIR	6-8
Populate Log Form Data	9-10
Connect your mobile device to the LionEight ELD device	11-12
Record Hours of Service	13

DOT Inspection

Inspect Logs	14
Data Transfer	15

Malfunction Responsibilities

Carrier Responsibilities Regarding Malfunctions	16
Record Keeping Responsibilities by the driver	16


ELD Malfunctions

ELD Malfunctions	17 - 19
----------------------------------	---------


Installation & Connection

Install the LionEight ELD device in your vehicle


1. With engine off, locate the diagnostic port inside the vehicle. It is located in one of the four places:



2. Attach the device to the diagnostic port of the vehicle.



3. Once the device is installed, ensure the device is working properly as evidenced by a green LED light blinking. The green light starts blinking after a GPS & Cellular connection is initiated.




4. Mount your device away from electrical components (they may cause interference).

Installation & Connection

Install the LionEight ELD App

1. For android phones and tablets download the LionEight ELD App from Google Play Store. For iPhones and iPads download the LionEight ELD App from the App Store.
2. Open the LionEight ELD App.




Login to the LionEight ELD App and select a vehicle

Read the login details from your email. If you don't have login details yet, or you've forgotten them, contact your Carrier administrator.

1. Enter your login details and tap **LOG IN**, you will be prompt with Terms and Conditions.
2. Read the Terms and Conditions and tap **AGREE**.
3. Select your vehicle from the list, or search for one.
4. Tap **ACCEPT**, you will be prompt with a Settings page where you can review and edit settings details.
5. Tap **SAVE**.

! Dashboard View


After successfully login & vehicle selection, the Dashboard page is open. Use **Tap to Connect** bar to connect to your vehicle.



Installation & Connection


Complete Pre-Trip DVIR

Start a new pre-trip inspection report by tapping the **DVIR** button.



You can also Start Inspection from the left side menu by tapping the DVIR option.

1. From DVIR view, enter the odometer value and tap **Start Inspection**, if you are in **Off Duty** or **Sleeper Berth** status you will be placed to **On Duty** status. Pre-trip is selected by default.



2. Tap **Add/Remove** under Vehicle Defects and review each item from the list against your vehicle.

The screenshot shows a mobile application interface for a Driver Vehicle Inspection Report (DVIR). At the top, there are two tabs: 'Pre-Tip' (selected) and 'Post-Tip'. Below the tabs, there are three input fields: 'VIN' with the value 'WS3KN3U33A334456', 'Odometer', and 'Location' with the value 'San Francisco'. Below these fields is a section titled 'Vehicle Defects' which currently displays 'No Defects Found'. A blue button labeled 'Add/Remove' is located to the right of the 'Vehicle Defects' section and is highlighted with an orange rounded rectangle.

3. If you identify a defect, select the appropriate defect in the list and enter a comment and photo. Tap **Save**.

The screenshot shows the 'Front' section of the DVIR form. It contains a list of vehicle components with checkboxes and dropdown arrows: 'Headlights', 'Flashers', 'Fog Lights', 'Marker Lights', and 'Engine Compartment'. At the bottom of the form, a blue button labeled 'Save' is highlighted with an orange rounded rectangle. The top of the screen shows the time '9:41', the title 'DVIR', and status icons for signal, Wi-Fi, and battery.



4. If Trailer is applicable, repeat step 2 and 3 under Trailer Defects.
5. Tap **Sign and Save the Report**.

The screenshot shows a mobile application interface for a report. It features a light gray background with several white rectangular sections. At the top, there is a section labeled 'Odometer'. Below it is a section labeled 'Location' with the text 'San Francisco' underneath. The next section is 'Vehicle Defects', which includes a blue 'Add/Remove' button and the text 'No Defects Found'. Below that is a 'Trailer Defects' section, also with a blue 'Add/Remove' button and the text 'No Defects Found'. At the bottom of the form is a large blue button with the text 'Sign and Save the Report', which is highlighted by a thick orange border.

Installation & Connection


Populate Log Form Data

Select **Trailer/Docs** button from your Dashboard to add the Trailer/Shipping Docs number.




Trailers & Shipping Docs are also available through the Logs folder.

1. From your Dashboard view, tap the ☰ icon.
2. Select **Logs**.
3. Tap the daily log at the top of the list.



4. Scroll down (to the bottom of the screen) and tap the **Trailer** or **Shipping Docs** field.
5. Enter your trailer or shipping doc numbers. You will see "Trailer saved" OR "Shipping Docs saved" confirmation message.




Installation & Connection

Connect your mobile device to the LionEight ELD device


! Enable Bluetooth

Please ensure that Bluetooth is enabled on your device before you connect to the LionEight ELD device.


In the main Dashboard view there is **Tap to Connect** bar - just below the vehicle number



1. Use **Tap to Connect** bar to connect to your vehicle. The device will attempt to connect to selected vehicle ELD via Bluetooth. ELD bar will change from red to orange: **Pairing**.



2. An icon (📶) will appear in connection bar upon successful connection.



✓ Ready to Drive


Once you've completed all of the pre-trip tasks in this section, you're ready to drive.

When your vehicle is moving at 5 MPH or greater, your duty status will automatically switch to **Driving**, in accordance with the ELD mandate.


Installation & Connection

Record Hours of Service

1. When your vehicle reaches 5 MPH or greater, LionEight ELD is indicating that vehicle is **In Motion** and your duty status will automatically change to **Driving**.



2. When the vehicle stops (0 MPH) it's considered **Stationary**.




3. You can change your duty status by tapping the **Driving** and selecting some other duty status.
4. If your vehicle remains **Stationary** for five minutes you will be prompted with a question if you would like to change your duty status. If you ignore this question your duty status will be changed to **On Duty**.


DOT Inspection

Inspect Logs

To begin the DOT inspection tap the menu icon on the top left and select the **DOT Inspection**



1. To let an officer inspect your logs tap **Begin Inspection**. Logs for current and last seven days will appear on the screen.




2. Hand the officer your mobile device.

DOT Inspection


Data Transfer

If the officer asks for the output file tap **Transfer Data**

1. Tap the **Transfer Data** to send the file via web service or email.



2. Select **Web Service** or **Email** transfer method.
3. A DOT officer will provide the **Output File Comment**, enter it in the text box.
4. Tap **Send**.



5. You will receive a confirmation if the file was submitted successfully. If it was unsuccessful, you will receive the following message: "ELD File Sending Failed. Use a different Transfer Data method or try again."

Malfunction Responsibilities

Carrier Responsibilities Regarding Malfunctions

The carrier must:

Provide drivers with an instruction sheet describing the various ELD malfunction events and record-keeping procedures (this document)

Provide drivers with a supply of 8 days' worth of blank paper driver records

Repair, replace or service

The motor carrier must correct the malfunction of the ELD within 8 days of discovery of the condition

OR

a driver's notification to the motor carrier, whichever occurs first

Record Keeping Responsibilities by the driver

The driver must:

Malfunction Events

Note the ELD malfunction and provide the carrier with written notice within 24 hours.

Reconstruct driving events for the current 24 hour period and previous 7 consecutive days using paper logs.

Continue to manually prepare driving logs until ELD is serviced and brought back into compliance.

During inspections which take place when a malfunction has occurred: provide safety official with manually kept driver logs.


Data Diagnostic Events

The driver must follow the motor carriers and ELD provider's recommendations in resolving the data inconsistency.

ELD Malfunctions

Diagnostic and Malfunction events show up in the application's header (top right) as a capital D and capital M. The **D** stands for diagnostic events and the **M** for malfunction events.

Tap **D** (diagnostic data) or **M** (malfunction) to view error details.



Malfunction

- ! ELD has reported Power compliance malfunction. Contact your manager immediately. Please stop using the LionEight ELD and switch to paper logs until the ELD malfunction has been corrected.

Mon, Aug 25, 10:15 AM

- ! ELD has reported Engine Synchronization compliance malfunction. Contact your manager immediately. Please stop using the LionEight ELD and switch to paper logs until the ELD malfunction has been corrected.

Mon, Aug 25, 10:15 AM

! ELD has reported Timing compliance malfunction.
Contact your manager immediately. Please stop using the
LionEight ELD and switch to paper logs until the ELD malfunction has
been corrected.

Mon, Aug 25, 10:15 AM

! ELD has reported Position compliance malfunction.
Contact your manager immediately. Please stop using the
LionEight ELD and switch to paper logs until the ELD malfunction has
been corrected.

Mon, Aug 25, 10:15 AM

! ELD has reported Data Recording compliance malfunction.
Contact your manager immediately. Please stop using the
LionEight ELD and switch to paper logs until the ELD malfunction has
been corrected.

Mon, Aug 25, 10:15 AM

! ELD has reported Data Transfer compliance malfunction.
Contact your manager immediately. Please stop using the
LionEight ELD and switch to paper logs until the ELD malfunction has
been corrected.

Mon, Aug 25, 10:15 AM

Data Diagnostic

! ELD has identified the Power data diagnostic event.

Mon, Aug 25, 10:15 AM

! ELD has identified the Engine synchronization data diagnostic event.

Mon, Aug 25, 10:15 AM

! ELD has identified the Missing required data diagnostic event.

Mon, Aug 25, 10:15 AM

! ELD has identified the Data transfer data diagnostic event.

Mon, Aug 25, 10:15 AM

! ELD has identified the Unidentified data diagnostic event.

Mon, Aug 25, 10:15 AM

Powered by



LionEight